

DVB-S SD & MPEG-2

MODEL No.: S-N316A

Main Features:

- MPEG-II & DVB-S Compliant.
- Max. 1500 channels receivable.
- Installation Wizard helps easy and automatic installation step by step.
- DiSEqC Control version 1.0 and 1.2 compatible.
- Timer Setting Supports automatic Turn-Off daily.
- Multi-Language support.
- OSD dynamic color.
- Parental lock function for menu and selectable per channel.
- Fun games and calculator.
- 2 CVBS signal output by RCA.
- Serial connection (RS232) data transmission.



Technical specification:

- Chipset and Memory: CPU: GX6101D(108MHz)
Flash: 8Mbit
RAM: SDRAM 16Mbit
- Power: Input: AC90~240V 50/60Hz
Operating: 9W
Max: 15W
Standby: ≤8W
- Interface: Tuner: 1 Input with loop through
RCA: 2 Video, 2 Audio(L/R)
SCART: 1 CVBS, 2 Audio(L/R)
USB2.0 port: 1 Output
RS-232: 1 DB-9F
- Tuner&Demodulation: Tuner: RDA5812
Demodulation: QPSK(SCPC/MCPC)
- Video Decoding: Compliant with: ISO/IEC13818-2, ISO/IEC11172-2 MP@ML and less
Maximum Video data rate: 15Mbps
Video Resolution: 720 x 576@ PAL, 720 x 480@NTSC
- Audio Decoding: Compliant with: ISO/IEC11172-3, Layer I/II, ISO/IEC13818-3, Layer I/II
Sampling rate: 32,44.1, 48KHz

